

PATTERN PLAY



Construction	Tufted Loop Pile
Face Fibre	100% Nylon
Stain Resistance	StainSmart® for stain resist and soil release
Finished Face Weight	410 g/m ²
Gauge	39.4 / 10 cm
Rows	56 / 10 cm
Tuft Density	220,472 /m ²
Finished Pile Height	3.0 mm
Standard Backing	WellBAC® Comfort 95% recycled open cell polyurethane cushion backing. Available with TractionBack® on request
Nominal Total Thickness	8.9 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	3800 g/m ²
Tiles per Box	22 (5.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	30 dB ΔL_w
Sound Absorption (ISO354)	0.30 Class D
Alpha p values	125Hz 0.00, 250Hz 0.05, 500Hz 0.35, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.40

ENVIRONMENTAL

61% recycled content by total product weight	15 year wear warranty
Manufactured in location certified to: ISO9001:2015 / ISO14001 / ISO45001 / ISO50001 using renewable electricity	Lifetime Antistatic guarantee
M/PACT™ Carbon Offset Floors, 7.36 kg CO ₂ e/m ² Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set	Latent Defects guarantee

WARRANTIES

INSTALLATION
