

# COLOUR COMPOSITIONS

Colour Compositions



Construction	Tufted, Textured Loop Pile
Face Fibre	ECONYL® 100% recycled Nylon
Stain resistance	StainSmart® for stain resist and soil release
Finished Face Weight	490 g/m <sup>2</sup>
Gauge	47.2 / 10 cm
Rows	44 / 10 cm
Tuft Density	207,680/m <sup>2</sup>
Finished Pile Height	2.5 mm
Standard Backing	WellBAC® Comfort 90% recycled open cell polyurethane cushion backing. Available with TractionBack® on request
Nominal Total Thickness	8.3 mm
Plank Size	25 cm x 100 cm
Nominal Total Weight	4000 g/m <sup>2</sup>
Planks Per Box	12 (3m <sup>2</sup> )

## PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class Bfl-s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	31 dB ΔL <sub>w</sub>
Sound Absorption (ISO354)	0.25 Class E
Alpha p values	125Hz 0.01, 250Hz 0.07, 500Hz 0.59, 1000Hz 0.18, 2000Hz 0.26, 4000Hz 0.36

## ENVIRONMENTAL

69% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,  
4.36 kg CO<sub>2</sub> e/m<sup>2</sup> Embodied Carbon (EPD calculation A1-A3)  
Cradle to Gate footprint 100% off set

## WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

## CERTIFICATIONS


## INSTALLATION

Ashlar Random	Herringbone

## CE / UKCA

DOP-2895-1004-02 BS EN 14041	DOP-0338-1004-02 BS EN 14041					