

COMFORTABLE CONCRETE 2.0

Milliken™

Laid Bare / Urban Drama / Urban Poetry

Construction	Tufted, Level Loop Pile
Face Fibre	Nylon
Stain Resistance	StainSmart® for stain resist and soil release
Finished Face Weight	600 g/m ²
Gauge	39.4 / 10 cm
Rows	39.4 / 10 cm
Tuft Density	155,118 /m ²
Finished Pile Height	3.3 mm
Standard Backing	WellBAC® Comfort Plus 90% Recycled Open Cell Polyurethane. Available with TractionBack® on request
Nominal Total Thickness	9.9 mm
Nominal Total Weight	4100 g/m ²
Plank Size	50 cm x 100 cm
Planks per Box	6 (3m ²)
Tile Size	50 cm x 50 cm
Tiles per Box	20 (5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class Cfl – s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A – Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	33 dB ΔL _w
Sound Absorption (ISO354)	0.30 Class D
Alpha p values	125Hz 0.00, 250Hz 0.10, 500Hz 0.40, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.40

ENVIRONMENTAL

59% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,
8.98 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3)
Cradle to Gate footprint 100% off set

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

													
													

INSTALLATION

CE / UKCA

									
Monolithic	Monolithic	Brick	Herringbone	DOP-2895-1004-01 BS EN 14041	DOP-0338-1004-01 BS EN 14041				