

LVT - ORIGINAL COLLECTION

Eero / Heritage Wood /
Polished Concrete / PowerGrid



Construction	High Performance Luxury Vinyl Tile
Finish	ProGuard MAX™ UV-Cured Urethane
Wear Layer Thickness	0.55 mm
Overall Thickness	5 mm
Edge Profile	Micro Bevel
Product Weight	8900 g/m ²

PERFORMANCE

Flammability/Smoke Emissions (EN 13501-1)	Class Bfl-s1
Use Classification (EN ISO 10874)	Class 33 Heavy Commercial Use, Class 42 General Industrial Use
Dimensional Stability (EN ISO 23999)	≤0.25 % (typically ≤0.10 %); Curl ≤2 mm
Residual Indentation (EN ISO 24343-1)	≤0.1 mm
Colour Fastness to Light (EN ISO 105-B02)	≥6
Castor Chair Resistance (Type W) (EN ISO 4918)	Pass
Chemical Resistance (EN ISO 26987)	Excellent
Electrostatic Performance (EN 1815)	≤2 kV
Impact Sound Insulation (EN ISO 717-2)	4 dB ΔL _w
Slip Resistance (EN16165 Annex B) (Ramp)	R10 (R11 Power Grid)
Slip Resistance (EN16165 Annex C) (Pendulum)	Eero ≥55 dry; ≥40 wet, Heritage Wood ≥58 dry; ≥49 wet, Polished Concrete ≥59 dry; ≥35 wet, PowerGrid ≥59 dry; ≥33 wet

INSTALLATION

Full spread of tackifier adhesive

ENVIRONMENTAL

20% recycled content by total product weight
(Pre Consumer internal waste)

Manufactured in ISO14001 certified location

M/PACT Carbon Neutral Floors,
23.52 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A4)
Cradle to Gate footprint 100% off set

Orthophthalate and REACH SVHC free- compliant to WELL feature
requirement for Enhanced Material Restrictions

WARRANTIES

15 year wear warranty

TILE/PLANK SIZE

Eero	228.6 x 1516.9 mm (9" x 59,72")
Heritage Wood	228.6 x 1516.9 mm (9" x 59,72")
Polished Concrete	457.2 x 914.4 mm (18" x 36")
PowerGrid	457.2 x 914.4 mm (18" x 36")

PLANKS PER BOX

Eero/Heritage Wood	6 (2.081 m ²)
Polished Concrete/PowerGrid	4 (1.672 m ²)

CERTIFICATIONS

INSTALLATION

Polished Concrete / PowerGrid	Eero / Heritage Wood	Heritage Wood
Half Drop	Ashlar Random	Herringbone

CE / UKCA

DOP 1004-05 EN 14041 ISO 10582	DOP 1004-05 EN 14041 ISO 10582	Bfl-s1	E1 HCHO	DS	DS