SPECIFICATION SHEET Date: 26.02.2024 Revision 1

PAINTED GARDEN RETOLD



Construction	Tufted, Textured Loop Pile
Face Fibre	ECONYL® 100% recycled Nylon
Soil Release	StainSmart® for stain resist and soil release
Finished Face Weight	490 g/m ²
Gauge	47.2 / 10 cm
Rows	44.0 / 10 cm
Tuft Density	207,874 /m²
Finished Pile Height	2.5 mm
Finished Pile Height Standard Backing	2.5 mm WellBAC® Comfort 90% Recycled Polyurethane cushion. Available with TractionBack® on request
	WellBAC® Comfort 90% Recycled Polyurethane cushion.
Standard Backing	WellBAC® Comfort 90% Recycled Polyurethane cushion. Available with TractionBack® on request
Standard Backing Nominal Total Thickness	WellBAC® Comfort 90% Recycled Polyurethane cushion. Available with TractionBack® on request 8.3 mm
Standard Backing Nominal Total Thickness Plank Size	WellBAC® Comfort 90% Recycled Polyurethane cushion. Available with TractionBack® on request 8.3 mm 25 cm x 100 cm

п	c	ח	Е.	\smallfrown	ח	А	А	Λ	NI	\boldsymbol{c}	С.
P	c	к	г	u	к	w	Λ.	м	IN	u	c
											_

Flammability (Euroclassification EN13501:1-2018)	Class BfI - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value \geq 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	31 dB $\Delta L_{\rm w}$
Sound Absorption (ISO354)	0.25 Class E
Alpha p values	125Hz 0.05, 250Hz 0.05, 500Hz 0.40, 1000Hz 0.20, 2000Hz 0.25, 4000Hz 0.35

ENVIRONMENTAL

70% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors, 4.36 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS































































INSTALLATION



Ashlar Random



CE / UKCA











